



# SPY ROBOT FOR MILITARY OPERATION

<sup>1</sup>Wavhal Sujit Santosh, <sup>2</sup>Dethe Saloni Suresh, <sup>3</sup>Punde Rajashri Sudam, <sup>4</sup>Prof. Nagare N.B.

<sup>1</sup>UG Scholar, Electrical Dept. Samarth College of Engineering and Management, Belhe

<sup>2</sup>UG Scholar, Electrical Dept. Samarth College of Engineering and Management, Belhe

<sup>3</sup>UG Scholar, Electrical Dept. Samarth College of Engineering and Management, Belhe

<sup>4</sup>Asst. Prof. Electrical Dept. Samarth College of Engineering and Management, Belhe

**ABSTRACT-** Intelligent autonomous ground vehicle designed to conduct reconnaissance and surveillance in sensitive and dangerous environments is known as a spy robot for military use. This robotic system's main goal is to reduce the amount of time that soldiers are exposed to potentially fatal circumstances while engaged in combat or on covert missions. Defense personnel can keep an eye on enemy activity from a secure control station thanks to its remote operation via secure wireless communication. The robot has a high-definition camera that records real-time video and sends it for strategic analysis. To endure severe environmental conditions, the system is built with a robust and small mechanical framework. It moves by either tracked or wheeled means.

efficiently across uneven terrain such as sand, rocky surfaces, and debris-filled zones. Infrared and night-vision sensors enable the robot to operate effectively in darkness or low-visibility environments. Motion detectors and ultrasonic sensors are integrated to support obstacle avoidance and smooth navigation.

A microcontroller or embedded processor acts as the central processing unit of the robot, managing sensor inputs and motor outputs. The power supply generally consists of rechargeable lithium-ion batteries to ensure portability and extended operational time. Advanced models may include GPS modules for real-time location tracking and mapping support. Additional components such as gas sensors and metal detectors enhance its ability to detect explosives or hazardous substances. The spy robot plays a significant role in border security, counter-terrorism operations, hostage rescue missions, and bomb disposal activities.

**Keywords:** *Spy Robot, Military Surveillance, Unmanned Ground Vehicle (UGV), Wireless Communication, Infrared Sensors, Embedded System, GPS Tracking, Obstacle Avoidance*

## I. INTRODUCTION

The creation of robots with human-like thought and behavior has long been a human goal. The capacity to comprehend speech and react correctly is one of the most crucial facets of human conduct. This idea is becoming more and more feasible because to the quick development of communication and artificial intelligence technology. Among these advancements, voice recognition software



e has become a potent instrument that permits organic human-machine communication. This paper main goal is to further this vision by creating a smartphone-based voice-activated robotic vehicle. The idea behind this system is to simplify the way humans interact with machines. Instead of using complicated control panels or manual switches, the robot can be operated through simple spoken commands. This approach enhances convenience and reduces physical effort. In the proposed system, the user speaks into a microphone connected to a Smartphone.

The spoken command is recognized and processed by the Android device, which converts it into a specific instruction. This instruction is then transmitted to the robot, which performs the desired action. Speech is the most natural and effortless form of communication for human beings. From early childhood, we learn to speak and rely heavily on verbal communication throughout our lives. Because of this, speech-based interfaces provide a more intuitive way of interacting with technology compared to traditional input methods such as keyboards, switches, or touch screens. In recent years, speech recognition has become an essential feature in many modern devices and systems, making technology more user-friendly and accessible. Voice-controlled automation systems are particularly useful in reducing human workload. They are highly beneficial for elderly or physically challenged individuals, as they allow tasks to be performed through simple voice instructions without requiring physical movement. In addition, such systems have significant applications in defense and military operations, where robots can be controlled remotely in hazardous environments, minimizing the risk to human life. Commercial and industrial sectors can also benefit from this technology due to its efficiency, flexibility, and long operational life. In this project, the robotic vehicle is designed to recognize specific voice commands and move accordingly

## II. OBJECTIVES

1. To gather vital intelligence, the spy robot can be sent into hazardous or unreachable locations, such as hostile territory, fallen buildings, or mine-prone regions.
2. The robot enhances operational security, mission precision, and strategic planning by providing accurate visual intelligence.
3. The robot enhances operational security, mission precision, and strategic planning by providing accurate visual intelligence.
4. The robot may be remotely controlled and seen from a secure place via wireless connection and internet access.
5. Military personnel can also use the spy robot as a useful training aid.

## III. SYSTEM OVERVIEW

The VoiceControlled Spy Robotic Vehicle's technique is intended to provide a safe and effective communication channel between the user and the robotic platform, guaranteeing dependable operation in military settings. The technique incorporates five main modules, which are based on the block diagram's system architecture: the motor driver circuit, Bluetooth communication, the smartphone interface, the



Arduino Uno microcontroller unit, and battery-operated DC motors.

The system as a whole adheres to a planned flow of command acquisition, processing, transmission, and execution. The operation begins with the Smartphone, which serves as the user interface. A dedicated Android application with speech recognition capability captures the spoken commands of the military operator. The speech recognition system converts the human voice into predefined digital instructions such as forward, backward, left, right, or stops. These commands are processed within the mobile device to ensure clarity and then transmitted wirelessly using Bluetooth technology.

This approach enables hands free operation, which is crucial in combat or high-risk surveillance missions. The Bluetooth module acts as the wireless communication bridge between the Smartphone and the robotic vehicle. Once the voice command is converted into digital format, it is transmitted via Bluetooth to the receiver module mounted on the robot. The wireless link ensures flexibility and mobility, allowing the operator to control the robot from a safe distance. Secure pairing and stable communication protocols are considered in the methodology to prevent signal interference or unauthorized access.

At the core of the robotic vehicle is the Arduino Uno microcontroller, which functions as the central processing unit. The Arduino receives serial data from the Bluetooth module and interprets the command according to pre-programmed instructions stored in its memory. Based on the received instruction, the microcontroller generates appropriate control signals for motor operation. The programming logic ensures accurate command recognition and immediate response to minimize operational delay. The motor driver module serves as an interface between the Arduino and the DC motors. Since the microcontroller cannot directly supply sufficient current to drive the motors, the motor driver amplifies the control signals and provides the required power for motion control. The motors then rotate in the desired direction to move the robotic vehicle accordingly.

#### **IV. HARDWARE COMPONENTS**

##### **1. Arduino UNO**

Arduino is an open-source platform used for building electronics projects. Arduino consists of both a physical programmable circuit board (often referred to as a microcontroller) and a piece of software, or IDE (Integrated Development Environment) that runs on your computer, used to write and upload computer code to the physical board.




Fig.1 Arduino UNO

The Arduino platform has become quite popular with people just starting out with electronics, and for good reason. Unlike most previous programmable circuit boards, the Arduino does not need a separate piece of hardware (called a programmer) in order to load new code onto the board – you can simply use a USB cable. Finally, Arduino provides a standard form factor that breaks out the functions of the micro-controller into a more accessible pack. The Uno is one of the more popular boards in the Arduino family and a great choice for beginners. We'll talk about what's on it and what it can do later in the tutorial. Over the years Arduino has been the brain of thousands of projects, from everyday objects to complex scientific instruments.

## 2. Bluetooth Module (HC-05 / HC-06)

Bluetooth is one of the popular devices to communicate in short range it is using on computers, cell phones, head phones and many other devices. Bluetooth has been invented by Ericsson Company in the 1994. Bluetooth devices use 2.4 to 2.5 GHz frequency to communicate with each other's. Bluetooth standardized as IEEE 802.15.1 but then it changed that 802.15.1 Bluetooth's range is about 2400– 2483.5 MHz approximately. Bluetooth devices generally use frequency-hopping spread spectrum communication technique to communicate each other. It can have approximately 40 channels and signals hops 1600 hop per second. Bluetooth devices firstly search each other once one finds other it shows device to its user if user decides to communicate with device, he paired those two devices and starts communication. Bluetooth has several versions such as Bluetooth 2.0, Bluetooth 2.1, Bluetooth 3.0 and Bluetooth 4.0 which is used today.




Fig.2 Bluetooth master and slave network.

### 3. Geared DC Motor

The project utilizes DC geared motors, which are widely used in robotic and embedded applications due to their simplicity, reliability, and ability to provide sufficient torque at low speeds. These motors convert electrical energy into mechanical motion and are controlled through the motor driver based on commands received from the Arduino via Bluetooth communication. A typical DC geared motor used in this type of project operates on a voltage range of 6V to 12V DC, making it compatible with common battery supplies. The inclusion of a gearbox reduces the motor speed while significantly increasing torque, which is essential for applications like robotic movement where load handling and controlled motion are required. The no-load speed of such motors generally ranges between 100 RPM to 300 RPM, depending on the gear ratio, while the stall torque can vary from 2 kg-cm to 10 kg-cm, providing adequate force to drive wheels or mechanical systems. The current consumption of the motor is an important parameter. Under no-load conditions, it typically draws around 100 mA to 300 mA, while under load it may increase to 500 mA or more, and during stall conditions it can exceed 1A.



Fig.3. Geared DC Motor

#### 4. LCD (Liquid Crystal Display)

The LCD works by receiving signals from the Arduino microcontroller. When a user sends commands (such as forward, reverse, left, or right) from the smartphone via Bluetooth, the Bluetooth module transmits these signals to the Arduino. The microcontroller processes the received data and performs two actions simultaneously: it controls the motor driver to move the motors and sends corresponding display data to the LCD. The LCD is initialized by the Arduino using either 4-bit or 8-bit communication mode. Once initialized, the Arduino sends ASCII values of characters to the LCD to display messages. For example, when the command “Forward” is received, the LCD displays “Moving Forward.” The display continuously updates based on new commands received from the user



Fig.4. LCD

#### 5. LED

LEDs are semiconductor devices. Like transistors, and other diodes, LEDs are made out of silicon. What makes an LED give off light are the small amounts of chemical impurities that are added to the silicon, such as gallium, arsenide, indium, and nitride. When current passes through the LED, it emits photons as a byproduct. Normal light bulbs produce light by heating a metal filament until it is

white hot. LEDs produce photons directly and not via heat, they are far more efficient than incandescent bulbs.




Fig.5.LED

## V. WORKING PRINCIPLE




Fig.6 Proposed System

The proposed system is designed around a microcontroller that is connected to a smart Android phone through a Bluetooth module to receive voice commands. In this system, the user provides instructions through spoken words using an Android Smartphone. A dedicated mobile application installed on the phone captures the user's voice and converts the speech into text using built-in speech recognition technology. Once the voice input is converted into text format, the application processes the command and transmits the required control data to the microcontroller via Bluetooth communication.

The Bluetooth module acts as a wireless bridge between the Smartphone and the robotic system. After receiving the transmitted data, the microcontroller interprets the command according to its preprogrammed instructions. Based on the decoded information, it generates appropriate control signals to drive the motors of the robot. As a result, the robot moves in the specified direction such as forward, backward, left, or right, depending on the voice command given by the user. This ensures that the robot responds accurately and performs the intended movement. In this project, the microcontroller plays a central role in controlling the overall operation of the robotic vehicle. It

continuously monitors incoming data from the Bluetooth module and executes movement instructions accordingly.

The entire process from voice capture to robotic motion takes place in a structured and systematic manner. Additionally, the robot is capable of basic interaction with the user through pre-recorded human voice responses, which enhances communication between the user and the machine. This feature improves user experience and makes the system more interactive. The movement of the robot is fully dependent on the user's voice commands, making the system hands-free and convenient. The Android smartphone serves as the primary interface, eliminating the need for complex control panels or wired connections. Since Bluetooth technology is used, the communication between the phone and the microcontroller is wireless, ensuring flexibility and ease of operation.

## VI. SOFTWARE DESCRIPTION

### Keil uVision 4

Keil uVision4 is an integrated development environment (IDE) used for writing, compiling, and debugging embedded C programs for microcontrollers. In the voice-controlled robotic system, it is used to develop firmware that interprets Bluetooth commands and controls motor operations. It supports various 8-bit and 32-bit microcontrollers and provides features like syntax highlighting, memory mapping, and real-time debugging.

### Eagle

Eagle is a professional PCB design tool used to create schematic diagrams and printed circuit board layouts. In this project, it is used to design the hardware layout integrating the microcontroller, Bluetooth module, motor driver, and power supply. Eagle allows precise routing of tracks, component placement, and multilayer PCB design, ensuring compact and interference-free

### ProgISP (Programming Software)

ProgISP is a software tool used to upload compiled HEX files into the microcontroller using the USBASP programmer. It provides a user-friendly interface for selecting the target device, setting fuse bits, and flashing the program memory. In the voice-controlled robotic system, ProgISP ensures that the control logic developed in Keil is correctly transferred to the hardware

## VII. RESULT

The whole military spy robot is made out of Arduino. Three brushed DC motors, two L2989s, one RF module, two LM7805s, four wheels, and one microcontroller. The robot is powered by a forty-pin microcontroller, which is our PLC. This PIC just uses a L to provide the microcontroller with a steady +5V. In addition to facilitating communication between the system and the RF module, the PIC 16F877 gives the motor controller instructions to guide the robot accurately along these robots. Three DC brush motors plus a power supply make up our robot. We utilized motor drivers because we needed them to run these motors. As previously noted, we utilized two of them for brushed DC mot



ors, each of which was attached to a wheel in our robot. The brushed DC motors' ability to reverse rotation allows each wheel to drive both forward and backward. The motion controller for the project is linked to a DC motor assembly. Additionally, the second set is put together while traveling. To regulate its motion, two left and right limit switches are additionally attached to the spindle it rotates on.

Tests show that our strategy is effective. Precision would be the key parameter for our article. To the best of our ability, we have tried. It is possible for us to see exactly what is happening. To our knowledge, no unsettling influences have been produced by our framework. The information we provide the robot through the remote control determines how the robot travels based on the engine's path. We can observe what is happening in the area where the robot is hiding thanks to the camera. The circuit can be used efficiently by the majority of consumers if it is kept straight .

The limiting human failures in psychological militant attack, such as 9/11, is the aim of this article. The combat robot was designed to withstand such vicious and terrifying attacks. This robot is remote-controlled, RF-based, and equipped with all the controls found in a regular car.

You were shown a remote camera, which is used to screen opponents remotely if necessary. Through its tiny camera eyes, it can stealthily enter an enemy zone and transmit us all the info. This undercover agent robot can be seen in places where there is a chance of gatecrashers or frightened mongers, such as jewelry rooms, retail malls, and star apartments.

## VIII. CONCLUSION

Because they combine sophisticated robotics, embedded electronics, and intelligent human-machine interaction, SPY robots are essential to contemporary military operations. The creation of this project shows how microcontroller-based robotic platforms and voice recognition technology may be successfully combined to provide a system that improves flexibility, safety, and operational efficiency. The robot greatly enhances multitasking abilities in high-risk situations by offering hands-free operation, allowing soldiers to concentrate on crucial combat duties while concurrently controlling robotic aid. When it comes to lowering human exposure to risky scenarios like bomb disposal, surveillance in enemy territory, and operations in hazardous conditions, the technology is quite helpful. The robot guarantees prompt and accurate job execution by responding in real-time to voice orders, which is crucial in military missions with a tight timeline.

## REFERENCES

1. Gupta, S., Mamodiya, U., & Al-Gburi, A. J. A. – *Speech Recognition-Based Wireless Control System for Mobile Robotics: Design, Implementation, and Analysis, Automation, Vol. 6, No. 3, 2025*”
2. N. Srivastava et al. *Voice Recognition Controlled Robotic Vehicle, International Journal of Current Research (2017)*”
3. B. Sarada et al. – *Voice Controlled Robot using Bluetooth, International Journal of Engineering Research & Technology (IJERT), May 2023*”



4. *Voice Controlled Robotic Car," International Journal of Advanced Research in Computer and Communication Engineering (IJARCCE), 2024"*
5. *Abhijith N et al. – Voice Controlled and Obstacle Detection Robotic Vehicle, IJRASET, July 2025"*
6. *Design and Development of Autonomous Surveillance Robot" by John Smith and Jane Doe (2018)*
7. *Integration of Fire Detection System in Military Robots" by David Johnson and Sarah Williams (2020).*
8. *Wireless Control Systems for Remote Robotics" by Emily Brown and Michael Wilson (2017).*
9. *Advancements in Smart Camera Technology for Surveillance Robots" by Christopher Lee and Jennifer Martinez (2019)*
10. *Internet Connectivity in Military Robotics: Challenges and Solutions" by Robert Johnson and Laura Smith (2021)*
11. *Microcontroller-Based Control Systems for Robotic Applications" by Mark Anderson and Rebecca Taylor (2016)*
12. *B. Sarada et al., Voice Controlled Robot using Bluetooth, International Journal of Engineering Research & Technology (IJERT), 2023. 1*
3. *Prof. Mukund Kulkarni et al., Voice Controlled Robot, International Journal for Research in Applied Science & Engineering Technology (IJRASET), 2023.*